UK Patent Application (19) GB (17) 2

(43) Application published 26 Aug 1987

(21) Application No 8704038

(22) Date of filing 20 F b 1987

(30) Priority data

(31) 8604164 8616137 (32) 20 Feb 1986

(33) GB

2 Jul 1986

(71) Applicants

Albright & Wilson Limited

(Incorporated in United Kingdom)

Albright & Wilson House, Hagley Road West, Oldbury. Warley, West Midlands.

Novo Industri A/S

(Incorporated in Denmark)

Novo Alle, DK-2880 Bagsvaerd, Denmark

(72) Inventors **Edward Tunstall Messenger** Arne Ditlev Fog **Anthony Martin**

Per Falholt

(51) INT CL* C11D 3/386

(52) Domestic classification (Edition I): C5D 6A4A 6A5A 6A5B 6A5C 6A5D1 6A5D2 6A5E 6A8 6A8B 6A9 6B10A 6B11A 6B11C 6B12B1 6B12C 6B12F1 6B12F2 6B12G1 6B12G2A 6B12L 6B12N1 6B12N2 6B13 6B14 6B1 6B2 6B4 6B7 6B8 6C8

(56) Documents cited

GB 1403173 GB 1386674

GB 1363027

EP A2 0163352

GB 1255284 EP A1 0040091

(58) Field of search

C5D СЗН

BAC

Selected US specifications from IPC sub-classes C11D

London SW1X 7QD

(74) Agent and/or Address for Service R. G. M. Savidge. c/o Albright & Wilson Limited, 1 Knightsbridge Green,

(54) Protected enzyme formulations for use in detergent compositions

(57) A protected enzyme system suitable for storage, prior to use, in a medium such as a liquid detergent which causes degradation of the unprotected enzyme, comprises an enzyme dispersed in a hydrophobic substance which does not dissolve on storage and which is liquid under the conditions of use, or the enzyme may be encapsulated in on or coated with a hydrophobic substance such as petroleum jelly. The enzymes may be those used in detergent compositions.

ONTV. 0 4 DEC. 1987 PATO

	Paraaf
pelb	Ged
·	V
	Delb

8734-D

SPECIFICATION

Pr tected enzym system

5 The present invention relates to protected enzyme systems which ar suitable for storage or use 5 in environments which tend to cause degradation f enzymes, such as liquid laundry detergents. Enzymes ar commonly employed as stain removing agents in powder detergents, but their incorporation in liquid cleaning preparations including liquid laundry detergents, such as those described for example in GB 2123846 and GB 2153380 has hitherto presented serious problems. 10 Those liquid formulations which are most effective for soil removal cause rapid degradation of 10 washing enzymes, often resulting in significant loss of stain removing properties after only a few days of storage. The relatively high alkalinity of the more effective soil removing formulations and the chemical action of most of the builder systems and surfactants present therein are particularly antagonistic to detergent enzymes and have largely prevented their use in such 15 detergents, but serious deterioration is observed even in comparatively non-alkaline compo-15 sitions, which have been specially formulated to permit incorporation of enzymes. Even in powder detergents some degradation of enzymes may be observed, especially if the powder is highly alkaline as in mechanical dishwashing powders, or contains an oxidising bleach such as p rborate. 20 We have now discovered that the deterioration of enzymes in hostile environments such as 20 liquid detergents is substantially reduced when the enzymes are dispersed in a hydrophobic material provided that the latter is insoluble in the particular environment. We have discovered,

m r over, that the protected enzyme is available to perform its normal function provided that th hydrophobic material is sufficiently fluid or friable to be disrupted under the conditions of 25 use.

According to one embodiment, therefore, our invention provides a protected enzyme system for storage prior to use, in an environment which causes progressive degradation of unprotected enzymes, said system consisting essentially of a dispersion of at least one enzyme in a hydrophobic substance which is insoluble in the said environment, and which is sufficiently fluid or & 30 friable to be disrupted under the normal conditions of use.

According to a preferred aspect our invention provides a protected enzyme system for use in a liquid cleaning composition said system comprising at least one detergent enzyme dispersed in a hydrophobic substance which is insoluble in the liquid detergent but dispersible therein as < particles or droplets, and which is sufficiently fluid or include to be disrupted under cleaning 35 conditions

According to a second embodiment our invention provides a protected enzyme system for use in a liquid cleaning composition consisting essentially of granules comprising at least one detergent nzyme encapsulated within a hydrophobic substance which is not soluble in the liquid cleaning composition and which is fluid or friable at normal wash temperatures.

Acc rding to a third embodiment our invention provides a protected enzyme system for use in liquid detergent compositions consisting essentially of a dispersion of a detergent enzyme in a hydrophobic liquid which is insoluble in liquid detergent.

According to a fourth embodiment our invention provides a method of protecting an enzyme for st rage prior to use in an environment which tends to cause progressive degradation of 45 unprotected enzymes, which method comprises dispersing the enzyme in a hydrophobic medium which is insoluble in said environment but dispersible therein as particles or droplets and which is fluid or friable under the normal conditions of use.

According to a fifth embodiment our invention provides a method of protecting enzymes which c mprises dispersing a detergent enzyme in a hydrophobic substance which is insoluble in liquid 50 detergent, and fluid at normal wash temperatures.

According to a sixth embodiment our invention provides a liquid cleaning composition having dispersed therein particles or droplets of a protected enzyme system of our invention as hereinbefore described.

References herein to solubility in a medium refer to both dissolution in an aqueous or other ? Menhon < 55 continuous s Ivent phase of the medium and solubilisation in surfactant micelles or any other discontinuous phas dispersed in the medium.

Th hydrophobic material may be an organo polysiloxane il, e.g. a poly di(alkyl)siloxane, wherein the alkyl gr up has preferably from 1 to 4 carbon atoms, especially a poly di(methyl)siloxane. Especially pr ferred ar hydrophobic liquids which have been stabilised by suspending.... O therein hydrophobic solid particles. Examples include the silicone compositions which have been prop sed for use as antifoam in liquid detergents which comprise hydrophobic silicone oil and hydrophobic silica, .g. a finely divided silica with a silicone at least partly bonded to the surface of the silica particles. For example a hydroxy functional organosiloxane may be condensed with the hydroxy groups of the silica surface. Examples of such compositions include those sold 65 under the Registered Trade Marks "WACKER" Antifoam S132. "BEVALOID" 4237, "UNION

25

granules

40

45

50

antifoam as hydropho be

cancel

CARBIDE" Y1206, or DIAMOND SHAMROCK'S "NOPCO" 8315. The silicone antifoam may be diluted with an unmodified silicone oil such as a poly dimethyl siloxane. Furthermore the viscosity of the silicone may be increased by addition of finely divided silica eg, fumed silica such as Degussa's "Aerosil" 200 (RTM)/

Alternatively the hydr ph bic material may b a high molecular weight hydrocarbon, e.g. petroleum bright stock or a s -called petroleum jelly, a high molecular weight alcoh i, e.g. more than 28 carbon atoms r a high molecular weight fluocarbon or a hydrophobic phosphate ester such as a mono- and/or di- fatty alkyl phosphate ester or a salt thereof, especially a sodium or calcium salt or a trialkyl or triaryl phosphate. Hydrophobic fluid materials may be further stabilised by inclusion of hydrophobic solid particles, e.g. those formed by condensing silica with silicone as described above or with a fatty alcohol. According to one embodiment the hydrophobic material may be a solid or waxy material at ambient temperature, which has a softening or preferably melting point below normal wash temperature, e.g. below 60°C, preferably below 50°C more usually 40°C, often below 30°C. Such solid materials provide products which are 15 particularly suitable for use in powder as well as liquid detergents. Typically we prefer that our hydrophobic material has a viscosity greater than 0.05 Pascal seconds at normal storage temperature (e.g. room temperature) preferably greater than 0.2, more preferably greater than 0.5 and most preferably greater than 0.8 Pascal seconds: In particular we prefer that the viscosity should be greater than 1 Pascal second e.g. greater than 2 Pascal seconds, especially greater than 10 20 Pascal seconds. We prefer that the viscosity should be less than 200 Pascal seconds, most preferably less than 100 Pascal seconds, e.g. less than 60 Pascal seconds and especially less than 40 Pascal seconds, at the temperature of use. Fluid materials having a viscosity between 1. and 50 Pascal seconds at ambient temperature are especially suitable.

Unless stated to the contrary, all references herein to viscosities are as measured at 24 sec $^{-1}$ 25 shear and at 25°C.

The enzyme may for example be a detergent enzyme, such as a protease, lipase, amylase, decarboxylase, or cellulase, such as those sold by Novo Industri AS under the Registered Trade Marks "SAVINASE", "TERMAMYL", "ESPERASE" and "ALCALASE", or other enzymes which are active in the removal or amelioration of soil or stains or a mixture of such enzymes.

The enzyme may be present in the hydrophobic material in the form of dispersed droplets of a solution of enzyme, e.g. in water or a lower, preferably water miscible, mono-, di- or polyhydric alcohol such as propylene glycol and optionally containing an enzyme stabiliser such as is known in the art. Enzyme stabilisers which may be present include lower alcohols, e.g. glycerol, lower mono- or di-carboxylic acids and their salts, especially formates and oxalates, borates and

Alternatively the enzyme may be present in the form of suspended particles of an enzyme-35 calcium salts. containing solid, the solid enzyme being preferably obtained by drying or precipitation from an enzyme solution, optionally containing a stabiliser as aforesaid, e.g. as described in US 3 723 250, particularly at column 12; EP 0 006 638, Example 2a and b GB 1,296,839; U.S. 40 4,435,307; EP 0 130 064 or Belgian Patent 889336.

The enzyme may also be present in a water soluble granule or marume. Typically this is the form in which enzymes are sold commercially. Thus a soluble crystalline carbohydrate such as sucrose or a salt such as sodium chloride, sodium carbonate or sodium sulphate may be granulated or marumerised with the enzyme, and, optionally, with enzyme stabilisers, e.g. as 45 described in U.S. 4,106,991 or GB 1,362,365, page 9, and the product dispersed in, or coated with, silicone or a hydrocarbon, such as petroleum jelly.

The enzyme may be incorporated in the inert oil by dispersion by simple stirring. Where the hydrophobic material is solid at room temperature it may first be melted before dispersing the enzymes and subsequently cooled to room temperature. Optionally the dispersion may be spray 50-cooled to provide a particulate product.

The proportion of enzyme in the protected enzyme system may be determined by the desired viscosity of the system, where it is desired to handle or store the latter as a liquid. Higher proportions tend to provide higher viscosities, but are less prone to sedimentation of the Sedimentation -> dispersed enzyme. H wever, we do not exclude the use of sedimenting systems provided that asily redispersed by stirring before the system is added to the detergent 55 the enzyme can b composition.

Preferably the particle size and proportion of the enzyme are chosen to provide an overall viscosity of the protected system greater than 0.1 Pascal seconds, typically greater than 0.5 Pascal s c nds especially greater than 1 Pascal second more preferably greater than 2 Pascal sec nds, e.g. greater than 3 Pascal seconds and optionally greater than 10 Pascal seconds, under the conditions of storage and less than 200 Pascal seconds, more preferably less than 100 Pascal seconds, e.g. less than 70 Pascal seconds under the conditions of use. Systems having a viscosity in the range of 2 to 60 Pascal seconds at ambient temp rature are generally preferred.

using PJ i adding structure by richusian of ملامر مح*نا*اده 10

mett-emp

15

20 lower then Vigosit of Oven caps Pambent.

25

35

Sabilizer

40

45

60

viscosity @ ausient kup

65.

particle size

55

JEDA K

of solid ensyme

in is incorporated in the system as a solution, the solution preferably contains 1

•	90% by weight of enzyme c ncentrate, e.g. 2 t 80%, typically 5 to 60%, and its dispersi n		
i	the oil typically contains 1-80, m re usually 5-70, preferably 10-60, more preferably 15-50,		
•	to 20-40 or 30-50% by weight of enzyme solution, the percentages being expressed by		
	veight of the total protected enzyme system. The suspension if solid enzyme concentrate in	_	
- 5 t	he hydrophobic material typically contains 1 t 90, m re usually 5 t 80, preferably 20-60,	5	
•	a 30-50 or 20-30% by weight of solid, based on the tital weight of suspension.		
_	The prop rtion of enzyme in the protected enzyme system may depend on whether the	d is	av1
ı	hydroph bic substance is required to perform any useful function in its own right, e.g. as	Ective	levelos
10	antifoam. Where a low foaming composition is required the enzyme and antifoam may conveniently be in the same relative proportions as those which are required in the final composition.	10 (butifoam?
10	Alternatively a more concentrated suspension of enzyme may be prepared and diluted with more		
•	antifoam prior to use, or added to the composition simultaneously with or separately from the		
	additional antifoam.		•
	Where the hydrophobic material is not required to perform a useful function other than	0.2	
15	protecting enzyme, the enzyme concentration may be the maximum which is consistent with a	15	
	manageable product. 90% by WAM		
	The particle size of the dispersed enzyme in the protected enzyme system can vary within		
	wide limits. Typically the dispersed enzyme may have a particle size in the range 1μ to 2mm,		
	preferably 5μ to 1mm, e.g. 10μ -700 μ . Solid enzyme concentrates tend to be in the lower part	20	
20	of the above range, liquid solutions are normally dispersed with a particle size in the middle of the range, e.g. 100μ - 800μ . Granular enzymes usually have a particle size in the upper part of		
	the range, e.g. 300μ -1mm. True for Owen? Upper limit is above final particle Size,		
	The protected enzyme system is generally readily dispersed in the liquid detergent by simple		
->	estirring. The system may be dispersed as particles or droplets of from 2μ to 2.5mm diameter,		
25	more usually 5μ - 500μ , preferably 10μ - 100μ , where a dispersed solution or concentrate of	25	
	enzyme is used as the protected system. Where the enzyme is present as a granulate, the		
	preferred particle size of the system in the liquid detergent is 500 μ to 1mm.		:
	Dispersants and emulsifiers may be used as required but are not usually preferred. Why? Preferably the composition is added to a liquid detergent which comprises an aqueous phase,		
20	surfactant, sufficient electrolyte dissolved in the aqueous phase to form with the surfactant, a	30	
30	structure capable of supporting suspended particles, and a protected enzyme system of our		
	inventi n. suspended in the detergent composition.		
	Preferably the composition contains an effective amount of a detergent builder. Suitable		
	builders include condensed phosphates, especially sodium tripolyphosphate or, less preferably,		
35	notassium pyrophosphate or sodium tetraphosphate, sodium carbonate, sodium silicate, sodium	35	
	orthophosphate, sodium citrate, sodium nitrilotriacetate, a phosphonate such as sodium ethylene-		
	diamine tetramethylene phosphonate, sodium aceto diphosphonate or sodium aminotris (methylene phosphonate), sodium ethylenediamine tetracetate or a zeolite. Other less preferred builders		
	include potassium or lithium analogues of the above sodium salts.		
40	The proportion of builder is typically from about 5% to about 40% by weight of the liquid	40	
70	detergent composition usually 10% to 35%, preferably 15%-30%, more preferably 18% to		
	28% most preferably 20 to 27%. Mixtures of two or more builders are often employed, e.g.		
	sodium tripolyphosphate with sodium silicate and/or sodium carbonate, or with zeolite, or so-		
	dium nitrilotriacetate with sodium citrate.	45	
45	Preferably the builder is at least partly present as solid particles suspended in the composition.	73	
	Particularly preferred are liquid detergent compositions according to the aforesaid GB 2,123,846 or GB 2,153,380.		
	The invention is also applicable to the preparation of unbuilt cleaning compositions or compo-		
	sitions in which all the builder is present in solution.		
50	The surfactant may be an anionic, nonionic, cationic, amphoteric, zwitterionic and/or semi	50	
	polar surfactant which may typically be present in concentrations of from 2 to 35% by weight of	f	•
	the composition, preferably 5 to 30%, more usually 7 to 25%, e.g. 10 to 20%.		
	Usually the composition contains an alkyl benzene sulphonate together with one or more other		
-	surfactants such as an alkyl polyoxyalkylene sulphate and/or a non-ionic surfactant. The latter	55	;
5:	may typically be an alkanolamide or a polyoxyalkylated alcohol. Other anionic surfactants include alkyl sulphate, alkane sulphonates, olefin sulphonate, fatty		
	ester sulphonates is any alkyl sulphosuccinates, alkyl sulphosuccinamates, taundes isetnionates		
	and polygovalkylene derivates of the aforesaid categories of anionic surfactant. In every case the		
	surfactant for use herein has an alkyl group with an average of from 8 to 22 preferably 10 t		
6 (O 20 e.g. 12 to 18 carbon atoms. Alkyl groups are preferably primary and straight chain, noweve	r 60	
	we do not exclude branched chain or secondary alkyl groups. In the case of alcohol based non-		
	ionics the branched chain are sometimes preferred.	a	
	The surfactant may be wholly or predominantly non ionic, e.g. a polyoxyalkylated alcohol alone or in admixture with a polyoxyalkylene glycol. Other non-ionic surfactants which may be used	-	
6	5 include polyoxyalkylated derivatives of carboxylic acids, glycerol, sorbitan, alkylphenols, alkylo-	65	5
	- money paryonyantyioted demices of defenty of the second		

65

lamides or amine oxides. All references herein to p lyoxyalkylene groups are preferably to polyoxyethylene groups, or less preferably to p ly xypropylene or mixed oxyethylene oxypropylene copolymeric or block copolymeric groups or to such groups with one or more glyceryl groups. Preferably the polyoxy-5 alkylene groups have fr m 1 to 30, m re usually 2 to 20, e.g. 5 to 15, alkyleneoxy units. 5 Cationic surfactants f r use according to our inventi n include quaternised alkyl amines, amid amines and imidazolines. Amphoteric surfactants include betaines and sulphobetaines. In general any surfactant referred to in GB 1,123,846, or in "Surface Active Agents and Detergents" by Schwartz, Perry and Berch, may be used. Preferably the pH of the liquid detergent composition is alkaline, e.g. about 7.5, especially 7.5 10 to 12 typically 8 to 11, e.g. 9 to 10.5. Preferably the liquid detergent composition contains dissolved electrolyte. This may comprise a dissolved portion of the builder and/or any other salt, inorganic or organic, which is not itself a surfactant and which salts out the surfactants present from solution (including micellar solution). 15 Examples include sodium chloride, sodium nitrate, sodium bromide, sodium iodide, sodium bo-15 rate, sodium formate, or sodium acetate, or corresponding potassium salts. Preferably, however, the electrolyte is a salt which is required to perform a useful function in the wash liquor. The electrolyte may comprise sodium sulphate in minor concentrations, but electrolyte mixtures containing concentrations of sodium sulphate of about 3% or over based on the total weight of 20 the detergent composition, are preferably not used because they give rise to undesirable crystal-20 The detergent composition may contain any of the usual minor ingredients such as soil lisation on standing. suspending agents (e.g. carboxymethyl cellulose), optical brightening agent, perfume, colouring and, optionally, a bleach. Particularly preferred liquid detergents are those containing long chain, e.g. C₁₀₋₁₄ linear alkyl 25 benzene sulphonates in an amount of 5-12%, long chain alkyl ether sulphates, e.g. with 1-5 ethyleneoxy units in amount of 0-3%, fatty acid alkanolamides, e.g. diethanolamides in amount of 1-5%, mixtures of mono and di long chain alkyl phosphates in amount of 0-3%, e.g. 0.1-1%, sodium tripolyphosphate (preferably pre-hydrated with from 0.5 to 5% by weight of 30 water) in an amount of 14-30%, e.g. 14-18% or 20-30% and optionally sodium carbonate in 30 an amount of up to 10%, e.g. 5-10%, with the total of sodium tripolyphosphate and carbonate of 20-30%, antiredeposition agents such as sodium carboxymethyl cellulose in amount of 0.05-0.5%, optical brightening agent in amount of 0.05-0.5%, chelating agents, e.g. amino phosphonates such as methylene phosphonates of di and polyamines especially sodium ethylene-35 diamine tetra[methylene phosphonate] or diethylene triamine hexa[methylene phosphonate] optionally present in amount of 0.1-1%, together with conventional additives such as perfume, the remainder being water, the percentages being by weight of the total liquid detergent. The liquid detergent may have a pH of 6 to 13, preferably 7 to 12, more usually 8 to 11, e.g. 9 to 10.5. The compositions of the invention may typically contain 0.01 to 10%, e.g. 0.05-0.5% by 40 40 weight of the protected enzyme system. Our protected enzyme systems are useful as additives to powder cleaning compositions. For instance enzyme dispersed in silicone antifoam or viscous hydrocarbon may be incorporated into a powder laundry detergent. Conventionally such powders may contain surfactant (usually in total amounts of from 5 to 30% by wt.), builder, a solid filler and optionally a bleach. Usually the 45 surfactant comprises a sodium alkyl (preferably C₁₂₋₁₄ linear) benzene sulphonate in amounts of 45 from 2 to 20%, preferably 5 to 15%, by weight of the total composition and optionally a sodium alkyl (e.g. C₁₂₋₁₂) polyoxyethylene (e.g. 2 to 10% mole) sulphate and/or a non-ionic surfactant such as an alkanolamide, e.g. coconut, mono- or di- ethanolamide and/or a polye-The builder is typically sodium tripolyphosphate although zeolites, sodium carbonate, sodium thoxylated fatty alcohol. 50 silicates, sodium citrate, sodium nitrilotriacetate and mixtures thereof may be present as well as or in place of sodium tripolyphosphate. The total amount of builder is usually between 10 and 40% by weight of the total powder, e.g. 20 to 30%. 55

40% by weight of the total powder, e.g. 20 to 30%.

The filler is typically sodium sulphate which may typically be present in a proportion of from 0 The filler is typically sodium sulphate which may typically be present in a proportion of from 0 to 60% usually 20 to 50% of the total composition in order to ensure a free flowing powder.

The bleach is normally a peroxy compound especially a perborate or percarbonate.

The bleach is normally a peroxy compound especially a perborate or percarbonate.

The powder also usually contains the usual minor ingredients such as soil suspending agent (typically sodium carboxymethyl cellulose) optical brightening agent and perfume and optionally colouring.

Protected enzyme systems according to our invention may be added to machine dishwashing powders, scouring creams and other hard surface cleaners, carpet shampoos, degreasing compositions, oven cleaners, dishwashing liquids, soap powders, laundry pre soak compositions and other cleaning preparations.

Dishwashing powders according to our invention may typically comprise a substantial propor-

min r proportion, e.g. 1 t 5%, of surfactant preferably a non-ionic surfactant such as an alkoxylated alcohol, together, optionally but preferably, with a builder such as sodium tripolyphosphate in pr portions of up to about 45% by weight of the composition, e.g. 20 t 35%, an alkaline silicate such as sodium metasilicate and an alkaline buffer such as borax. The compo-5 sition may optionally contain a bleach such as chl rinated trisodium phosphate and from 0.1 to 5 2% by weight of the protected enzyme system. Liquid dishwashing compositions of our invention typically comprise highly soluble builders such as potassium pyrophosphate, and/or potassium silicate in a total concentration of 10 to 30% by weight, surfactants, preferably non-ionic in concentrations of 0.2 to 5% by weight and 10 hydr tropes such as sodium xylene sulphonate, sodium toluene sulphonate or sodium benzene 10 sulphonate in concentrations of 1 to 10% by weight. Hard surface cleaners of our invention may typically comprise 1 to 10%, surfactant, typically non-ionic or anionic/nonionic mixtures, 1 to 10% hydrotrope and 2 to 10% soluble builder such as potassium pyrophosphate. Hard surface cleaners may also optionally comprise abrasives such 15 as silica, or calcium carbonate as arragonite or calcite suspended in a structural liquid. 15 Carpet shampoos according to our invention may according to our invention comprise relatively high concentrations, e.g. 5 to 20% by weight, of high foaming surfactants such as mixtures of anionic surfactants (e.g. alkyl sulphates) with foaming agents (e.g. alkanolamides). Oven cleaners according to our invention may be of the caustic type comprising, e.g. 4 to 20 12% of alkalis such as sodium hydroxide, and typically a high foaming anionic surfactant such as 20 a s dium alkyl ether sulphate, or else of the solvent based type containing e.g. 10 to 30% of a water miscible organic solvent such as a lower mon- di- or polyhydric alcohol or other alcohol, e.g. propylene glycol, and typically a non ionic surfactant, together preferably with a builder such as sodium tripolyphosphate. 25 Any difficulties in dispersing the protected enzyme system in any of the foregoing liquid formulations is generally avoided by addition of small amounts of conventional dispersants or suspending agents such as soluble gums or polyelectrolytes. Normal wash conditions for laundry detergents involve temperatures of from 50°C to 60°C and a wash liquor containing about 2 to 15 gm per litre of detergent composition under vigorous 30 agitation. Some detergents, however, are formulated and recommended for use at cool or 30 intermediate wash temperatures (20 to 30 or 30 to 40°C respectively), either for sensitive fabrics or energy saving. The invention is illustrated by the following Examples. 35 35 Example 1 A protease solution, sold under the Registered Trade Mark "Esperase" 8 OL. was dispersed in a mixture of equal parts by weight of an antifoam silicone oil having a viscosity of 22.57 Pascal seconds at 24 sec 1 and 25°C which contains a hydroxyl terminated polysiloxane condensed with solid fumed silica, and is sold under the Registered Trade Mark "Wacker" Antifoam S132, 40 and a neutral polysiloxane oil, sold under the Registered Trade Mark "Wacker" AK50. The 40 silicone mixture had a viscosity of 3.4 Pascal seconds. The dispersion produced contained 38% by weight of the enzyme solution, based on the total weight of dispersion and had a viscosity f 11.9 Pascal seconds at 24 sec 3 and 25°C. The dispersion was incorporated by thorough stirring into a liquid built detergent to give the 45 following formulation: 45 wt. % Sodium linear C₁₂ alkyl benzene sulphonate 9.3 Sodium linear C₁₂₋₁₈ alkyl ether sulphate containing an average of 3 ethyleneoxy units per molecule 50 1.85 1.85 Coconut diethanolamide Sodium tripolyphosphate 16.7 Sodium carbonate 6.7 Sodium carboxymethyl cellulose 0.9 55 Optical brightening agent 55 0.1 Enzyme dispersion € 3.

This formulation was compared with the same formulation without enzyme as Control for stain removal from a test sample of cotton stained with blood, milk and carbon (EMPA 116) at a concentration of 5gl⁻¹ in wash water containing 200ppm calcium carbonate at a wash temperature of 60°C for 30 minutes.

10.5-11.0

The following percentages stain removal were observed:

pН

5

10

15

20

25

30

35

40

45

50

			•	
	Control Freshly prepared formulation Formulation after standing 22 days at 30	36% 57% 52%		
5				
	Examples 2 and 3 A 25% by weight suspension was pre- trate (pr pared as described in U.S. Pate viscosity of 1.83 Pascal seconds, which			
10				
10	"NOPCO 8315" silicone detoamer. The suspension had a viscosity of 7.3 detergents to give the following formula	32 Pascal second tions:	s and was incorpor	ated into built liquid .
	•	Ex.2	Ex.3	
	o it is dedead begans culphonate	6%	7%	
15	Sodium dodecyl benzene sulphonate			
	Sodium linear C ₁₂₋₁₈ alkyl ether sulphate containing an average of		•	
٠.	3 ethyleneoxy units per molecule	2%		
	Coconut diethanolamide	1.5%	3% ···	
20	Mixture of mono and di C ₁₆₋₁₈ alkyl			
20	MIXING OF HIGHE BUG OF CHE-18 CIVI.	0.5%	0.5% -	

The protease activity of the formulation of Example 2 was 15.4 kilo Novo protease units (KNPU) per g.

0.5%

24%

0.1%

1.25%

0.2%

0.5%

0.3%

to 100%

about 9.0

0.5% -

24%

0.1%

1.25%

0.2%

0.5%

0.3%

to 100%

about 9.0

35 Examples 4 and 5

Perfume

Water

30 pH

50

phosphate ester

25 Optical brightening agent

Sodium tripolyphosphate

Sodium carboxymethyl cellulose

phosphonate) sodium salt

Enzyme suspension in silicone oil

Diethylene triamine penta(methylene

In the same manner as in Examples 2 and 3, a 25% by weight suspension of the "ESPER-ASE" (Reg. Trade Mark) protease solid concentrate in another silicone antifoam oil having a viscosity of 1.22 Pascal seconds ("BEVALOID" 4237) was prepared and incorporated in the built liquid as in Examples 2 and 3 to give the corresponding formulations Examples 4 and 5 40 respectively. The suspension had a viscosity of 3.66 Pascal seconds.

The protease activity of the formulation of Example 4 was 14.8 KNPU per g.

Storage Stability Tests

The stability of the formulations of Examples 2 and 4 on keeping at 37°C for 5 weeks were 45 determined and compared to that of a corresponding reference formulation to Example 2 with the same amount of enzyme but no silicone oil.

The residual proteolytic activity of each formulation was determined by the dimethylcasein (DMC) method described in Novo Publication AF 101/4-GB. The results are shown in the following table with activity expressed as a percentage of the initial activity of that formulation:

Residual Activity after time in weeks

	Formulation	2	4	5
55	Exampl 2	80%	70%	70%
	Example 4	85%	65%	63%
	Reference	33%	9%	n.a.

60 Examples 6 to 13

A number of alternative protected enzyme systems were each prepared by stirring 25% of solid enzyme concentrate into the hydrophobe and tested as shown in the following Table:

55

Example N	Enzyme	Trade Name of Hydr ph be	Chemical Type f Hydrophobe	Viscosity P Sec. of Hydrophobe	Viscosity of system in P. Sec.	
6	"TERMAMYL"	"BEVALOID"* 4237	Silicone oil + hydrophobic silica	1.22	2.44	
7	"SAVINASE"	••	••		2.74	
8	"ALKALASE""	**	••	**	2.13	
9	**	"WACKER"* S132+ "WACKER"* AK50	diluted with silicone oil		9.76	
10	"TERMAMYL"	••	••	•	10.06	
11 .	"ESPERASE"	"CATANEX"* 79	Petroluem bright stock	1.62	4.09	
12	"ESPERASE"	"VASELINE"	Petroleum jelly			
13	"ESPERASE"•	"EMPICOL"* 7062P	mixed mono/di C ₁₆₋₁₈ alkyl acid phosphate			
14	"ESPERASE"	"WACKER"* S132	Silicone oil+ hydrophobic silica	22.7		
Each of according activity a	red Trade Mark. Examples 6 to 14 g to Example 3. E and stain removal temperature.	each was found	to exhibit subs	tantially improv	ved retention of	enzyme
Example A dish	15 . washing powder	has the following	ng formulation:			
(Regist	hol 12 mole eth tered Trade Mark tripolyphosphate ed trisodium pho	"EMPILAN" KO	CMP 0705/F)	2% 30% 9%		
Borax	metasilicate			2% 8%		
S dium i Exampl	10 carbonate			0.5% balance		

		GB 2 100 004A	
· · · · · · · · · · · · · · · · · · ·		·	
30% Active aqueous sodium xylene sulphonate	100		
	. 10%		
AND THE PROPERTY OF THE PARTY O	oxylate 0.5%		5
(Registered Trade Mark "EMPILAN" KA880)	0.5% 1%		
Potassium hydroxide	15%		
Tetra potassium pyrophosphate	10%		
Potassium silicate	0.5%		40
Example 9	balance		10
Water			,
Example 17 A hard surface cleaner has the following formu	lation:		, 15
5 30% sodium xylene sulphonate	10%		
Pagistered Trade Mark ELIESUL SASO	1078	•	
80% synthetic alcohol 8 mole ethoxylate (Registered Trade Mark "EMPILAN" KA880)	2%		
200 andium laund stillfille	5%		20
n (Registered Trade Mark "EMPILAN SLOOP	5%		
Tetra potassium pyrophosphate	0.5%		
Example 12	balance		
Water			25
5 Example 18 A carpet shampoo has the following formulation	on:		
14% sodium lauryl sulphate+	25.0%		
1 40 Javria manaethanolamide Sulphiosuccinato			30
Registered Trade mark "EMPIMIN" 3119)	0.5%		
Example 8	Salance .		
Water			
Example 19	ion:		35
35 A carpet shampoo has the following formulat	ioii.		
28% sodium synthetic lauryl sulphate	5) 36%		
(Registered Trade Mark "EMPICOL" LX 288/	2%		40
Lauric isopropanolamide	0.5%		41
40 Example 13 Water	balance		
5lo 20			
An oven cleaner has the following formulation	on:		4
Nonylphenyl 9 mole ethoxylate	15%		
(Registered Trade Mark EMPLAN NO. 3)	20%		
Propylene giycol	10%		
Sodium tripolyphosphate	0.5%		•
50 Example 7 Water	balance		
Example 21			
An oven cleaner has the following formulati	On.		!
55		•	
27% lauryl ethersulphate (Registered Trade Mark "EMPIMIN" 27/T)	20%		
Sodium hydroxide (as solid)	8%		
Example 12	0.5%		
60 Water	balance		
CLAIMS	o pri rito uso as a disc	ontinuous phase dispers	ed
1 A protected enzyme system for Storag	degradation of unprotect	ed enzymes, said syster	n
in an environment which causes progressive	me in a hydrophobic mat	arial which is substantia	IIV.
RF comprision a dispersion of at least one critical			

GB 2 186 884A

		_
•	ins luble in the said environment, and which is sufficiently fluid r friable t be disrupted under the normal conditions f use.	
	2. A protected enzyme system for use in a liquid cleaning comp sition, said system comprising at least one detergent enzyme dispersed is a hydrophobic substance, which is substantially	
5	which is sufficiently fluid or friable to be disrupted under cleaning conditions.	5
	3. A system according t claim 2, comprising a hydrophilic solution of at least one detergent enzym dispersed in a hydrophobic liquid.	
10	4. A system according to claim 2 comprising particles of a solid composition which contain at least one detergent enzyme and which are dispersed in a hydrophobic liquid.	10
	5. A protected enzyme system for use in a liquid cleaning composition consisting essentially of granules comprising at least one detergent enzyme encapsulated within a hydrophobic substance which is not substantially soluble in the liquid cleaning composition and which is fluid or friable at normal wash temperatures.	
15		15
	7. A protected enzyme system for use in aqueous based liquid detergents, said system comprising at least one detergent enzyme dispersed in a hydrophobic substance which is	
20	substantially insoluble in said liquid detergents and which has a melting point below 60°C 8. A protected enzyme system according to claim 7 wherein said hydrophobic substance has a melting point below 50°C.	20
	9. A system according to claim 8 wherein said hydrophobic substance has a melting point bel w 40°C.	
_	10. A protected enzyme system consisting essentially of a detergent enzyme dispersed in a hydr phobic liquid which is substantially insoluble in aqueous based liquid laundry detergents. 11. A system according to any foregoing claim wherein the hydrophobic substance has a viscosity greater than 0.8 Pascal seconds at 24 sec 'shear and 25°C.	25
	12. A system according to claim 11, wherein the hydrophobic substance has a viscosity greater than 10 Pascal seconds at 24 sec. I shear and 25°C.	30
	13. A system according to any foregoing claim wherein the hydrophobic substance has a viscosity less than 200 Pascal seconds at 24 sec 1 shear and 60°C. 14. A system according to claim 13, wherein the hydrophobic substance has a viscosity less	
35	than 60 Pascal seconds at 24 sec 1 shear and 60°C.	35
	16. A system according to any foregoing claim having a viscosity greater than 2 Pascal seconds at 24 sec 1 shear and 25°C.	
10	17. A system according to claim 16 having a viscosity greater than 10 Pascal seconds at 24 s c ¹ shear and 25°C. 18. A system according to any foregoing claim having a viscosity less than 200 Pascal	40
	sec nds at 24 sec 1 shear and 60°C. 19. A system according to any of claims 16 to 18 having a viscosity of from 2 to 60 Pascal seconds at 24 sec 1 shear and 25°C.	
45	20. A protected enzyme system consisting essentially of a water soluble granule containing a detergent enzyme and coated with petroleum jelly.	45
•	21 A system according to any of claims 1 to 19 wherein the hydrophobic substance is a hydrocarbon.	
50	rgan siloxane polymer.)	50
- E	24. A system according to claim 23, wherein the hydrophobic material is a silicone antifoam. 25. A system according to either of claims 23 and 24 comprising particles of finely divided hydrophobic silica and a silicone oil.	
55	26. A system according to any of claims 1 to 19 wherein the hydrophobic substance is a hydrophobic phosphate ester. 27. A system according to any foregoing claim, wherein said enzyme comprises one or more	55
_	28. A method of protecting an enzyme for storage, prior to use, as a discontinuous phase	
60	dispersed in an environment which tends to degrad unprotected enzymes, which comprises dispersing the enzym in a hydrophobic mat rial which is insoluble in the said environment, and which is a liquid under the normal conditions of use and dispersing said hydrophobic material in said environment.	60
55	29. A method for protecting at least one detergent enzyme for use in a liquid detergent composition which comprises dispersing said enzyme in a hydrophobic material which is sub-	65

63. A hard surface cleaner according to either of claims 61 and 62 wherein the hydrotrope is

phate.

	an alkali metal benzene r alkyl benzene, sulph nate having up t 4 aliphatic carbon atoms.	
	The second dealth accurated to any of claims and the are	
	65. A scouring cream according to claim 64 containing up to 70% by weight of an abrasiv	
	suspended therein.	
5	66. A scouring cream according to claim 65 wherein said abrasive is silica or calcium	
	carbonate.	5
	67. An oven cleaner containing a protected enzyme system according to any of claims 1 to 27.	
	68. An oven cleaner according to plaim 67 possibility for the control of the cont	
10	68. An oven cleaner according to claim 67 containing from 2 to 15% by weight of sodium	
	or potassium hydroxide and from 2 to 15% by weight of anionic and/or non-ionic surfactant.	10
	69. An oven cleaner according to claim 67 containing from 5 to 20% by weight of a non-ionic and/or anionic surfactant, from 5 to 40% by weight of a water-miscible liquid lower	
	mono-, di- or poly-hydric alcohol or ether alcohol, and from 5 to 4554	
	mono-, di- or poly-hydric alcohol or ether alcohol, and from 5 to 15% by weight of a builder. 70. A carpet shampoo containing a protected enzyme system according to any of claims 1	
15	t 27.	
	71. A carpet shampoo according to claim 70 comprising from 2 to 20% by weight of anionic	15
	and/or non-ionic surfactants.	
	72. A carpet shampoo according to claim 71 wherein said surfactant is a mixture of an alkyl sulphate and an alkanologists.	
	The state of the s	
20	73. A carpet shampoo according to any of claims 70 to 72 company.	
		20
	The protected enzyme system according to any of claims 1 to 27 miles at the	
	The same of the selection to any of the examples	
	75. A composition according to any of claims 20 to 47 subsected to the second of the s	
25		
	76. A composition consisting essentially of a detergent entire dispersed in the constant of the control of the	25
	//- A composition according to any of claims 1 to 27 and 76 when the contract to the contract	
~~		
1	76. A composition according to claim 77 wherein said hydrophable and the	20
	TO THE TOUCH SECURICIS.	30
	79. A composition according to claim 78 wherein said hydrophobic fluid has a viscosity of	
	from 2 to 50 Pascal seconds.	
	Printed for the No.	

Printed for Her Majesty's Stationery Office by Burgess & Son (Abingdon) Ltd, Dd 8991685, 1987.
Published at The Patent Office, 25 Southampton Buildings, London, WC2A 1AY, from which copies may be obtained.